

Power Electric Tester

III. TH6600L Series Programmable Bidirectional DC Electronic Load

Features

- High power density: 3U high single machine power 5kW/10kW/15kW
- Master-slave mode parallel, expandable to 480kW
- High accuracy and high resolution, low ripple and low noise
- Load mode supports CV, CC, CR, CP automatic conversion
- Built-in function generator: built-in sine, triangle, arbitrary wave and other waveforms, support custom waveforms
- 7-inch 24-bit color TFT LCD capacitive touch screen, 800×480 resolution
- Linux operating system
- Photovoltaic simulation test: simple PV test, MPPT maximum power point tracking
- Data recording function: real-time recording of voltage, current and other information, and save to USB flash drive
- USB flash drive upgrade: update the instrument system through USB flash drive
- Support knob and cursor to accurately adjust the value
- Intelligent fan control, save energy and reduce noise
- Timing function: timing the instrument output
- Analog interface: for external analog control
- Protection: built-in hardware OVP, OCP, OPP and other protections, customizable alarm events
- Support SCPI and MODBUS protocols

NEW



RS232	GPIB	LAN	USB HOST	USB DEVICE
standard	standard	standard	standard	standard

TH6600L Series

Dimension(mm): 215(W)×125(H)×290(D)

Weight: 32.5kg

Application

- R&D and design verification general test
- New energy: solar cells, new power vehicles, electric bicycles
- Routine testing and maintenance of production line benches
- Automation equipment integration testing
- Solar PV simulation test
- Teaching laboratories
- LED testing
- Automotive wiring harness reliability test

Power Electric Tester

III. TH6600L Series Programmable Bidirectional DC Electronic Load

Specifications

Model		TH6680L-120-05	TH6680L-240-10	TH6680L-360-15
Rated Input (Load Mode)	Power	0-5kW	0-10kW	0-15kW
	Voltage	0-80V	0-80V	0-80V
	Current	0-120A	0-240A	0-360A
	Internal Resistance	0.02-25Ω	0.01-13Ω	0.006-10Ω
Setting Resolution	Voltage	10mV	10mV	10mV
	Current	0.1A	0.1A	0.1A
	Power	1W	1W	1W
	Internal Resistance	0.001Ω	0.001Ω	0.001Ω
Readback Resolution	Voltage	10mV	10mV	10mV
	Current	0.1A	0.1A	0.1A
	Power	1W	1W	1W
	Internal Resistance	0.001Ω	0.001Ω	0.001Ω
Setpoint Accuracy 12Months (25°C±5°C)	Voltage	≤0.1%FS	≤0.1%FS	≤0.1%FS
	Current	≤0.2%FS	≤0.2%FS	≤0.2%FS
	Power	≤1%FS	≤1%FS	≤1%FS
	Internal Resistance	≤1% of maximum resistance ±1% of maximum current		
Readback Accuracy 12Months (25°C±5°C)	Voltage	≤0.2%FS	≤0.2%FS	≤0.2%FS
	Current	≤0.2%FS	≤0.2%FS	≤0.2%FS
	Power	≤1%FS	≤1%FS	≤1%FS
	Internal Resistance	≤1% of maximum resistance ±1% of maximum current		
Ripple & Noise (20Hz-2MHz)	Differential Mode Voltage	≤200mVp-p and 16mVrms	≤320mVp-p and 25mVrms	≤320mVp-p and 25mVrms
	Differential Mode Current	≤80mArms	≤160mArms	≤240mArms
Remote Sensor Compensation		≤0.5%FS		
Energy Feedback Efficiency		≤93%		
Volume & Weight	Rack Mount (WxHxD) mm	430×133×703.5		
	Overall Dimension (WxHxD)mm	483×133×793.5		
	Weight (net weight)	18.5kg	25.5kg	32.5kg
Power Supply		342VAC-528VAC, 44-66Hz		

Power Electric Tester

III. TH6600L Series Programmable Bidirectional DC Electronic Load

Specifications

Model		TH66200L-70-05	TH66200L-140-10	TH66200L-210-15
Rated Input (Load Mode)	Power	0-5kW	0-10kW	0-15kW
	Voltage	0-200V	0-200V	0-200V
	Current	0-70A	0-140A	0-210A
	Internal Resistance	0.1-150Ω	0.05-75Ω	0.033-50Ω
Minimum resolution of setpoint	Voltage	10mV	10mV	10mV
	Current	0.01A	0.01A	0.01A
	Power	1W	1W	1W
	Internal Resistance	0.01Ω	0.01Ω	0.01Ω
Minimum resolution of readback value	Voltage	10mV	10mV	10mV
	Current	0.01A	0.01A	0.01A
	Power	1W	1W	1W
	Internal Resistance	0.0001Ω	0.0001Ω	0.0001Ω
Setpoint accuracy 12Months (25°C±5°C)	Voltage	≤0.1% FS	≤0.1% FS	≤0.1% FS
	Current	≤0.2% FS	≤0.2% FS	≤0.2% FS
	Power	≤1% FS	≤1% FS	≤1% FS
	Internal Resistance	≤1% of maximum resistance ±1% of maximum current		
Readback accuracy 12Months (25°C±5°C)	Voltage	≤0.1% FS	≤0.1% FS	≤0.1% FS
	Current	≤0.2% FS	≤0.2% FS	≤0.2% FS
	Power	≤1% FS	≤1% FS	≤1% FS
	Internal Resistance	≤1% of maximum resistance ±1% of maximum current		
Ripple & Noise (20Hz-2MHz)	Differential Mode Voltage	≤320mVp-p and 45mVrms	≤320mVp-p and 45mVrms	≤320mVp-p and 45mVrms
	Differential Mode Current	≤22mArms	≤44mArms	≤66mArms
Dynamic recovery time (50%-100% Load)		≤1.5ms		
Remote Sensor Compensation		≤5% FS		
Energy Feedback Efficiency		≤93%		
Volume & Weight	Rack Mount(WxHxD)mm	430×133×703.5		
	Overall Dimension (WxHxD)mm	483×133×793.5		
	Weight (net weight)	18.5kg	25.5kg	32.5kg
Power Supply		342VAC-528VAC, 44-66Hz		

Power Electric Tester

III. TH6600L Series Programmable Bidirectional DC Electronic Load

Specifications

Model		TH66500L-30-05	TH66500L-60-10	TH66500L-90-15
Rated Input (Load Mode)	Power	0-5kW	0-10kW	0-15kW
	Voltage	0-500V	0-500V	0-200V
	Current	0-30A	0-60A	0-90A
	Internal Resistance	0.5-1000Ω	0.25-500Ω	0.16-340Ω
Minimum resolution of setpoint	Voltage	10mV	10mV	10mV
	Current	0.01A	0.01A	0.01A
	Power	1W	1W	1W
	Internal Resistance	0.01Ω	0.01Ω	0.01Ω
Minimum resolution of readback value	Voltage	10mV	10mV	10mV
	Current	0.01A	0.01A	0.01A
	Power	1W	1W	1W
	Internal Resistance	0.0001Ω	0.0001Ω	0.0001Ω
Setpoint accuracy 12Months (25°C±5°C)	Voltage	≤0.1% FS	≤0.1% FS	≤0.1% FS
	Current	≤0.2% FS	≤0.2% FS	≤0.2% FS
	Power	≤1% FS	≤1% FS	≤1% FS
	Internal Resistance	≤1% of maximum resistance ±1% of maximum current		
Readback accuracy 12Months (25°C±5°C)	Voltage	≤0.1% FS	≤0.1% FS	≤0.1% FS
	Current	≤0.2% FS	≤0.2% FS	≤0.2% FS
	Power	≤1% FS	≤1% FS	≤1% FS
	Internal Resistance	≤1% of maximum resistance ±1% of maximum current		
Ripple & Noise (20Hz-2MHz)	Differential Mode Voltage	≤350mVp-p and 70mVrms	≤350mVp-p and 70mVrms	≤350mVp-p and 70mVrms
	Differential Mode Current	≤16mArms	≤32mArms	≤48mArms
Remote Sensor Compensation		≤5%		
Energy Feedback Efficiency		≤93%		
Volume & Weight	Rack Mount (WxHxD)mm	430×133×703.5		
	Overall Dimension (WxHxD)mm	483×133×793.5		
	Weight (net weight)	18.5kg	25.5kg	32.5kg
Power Supply		342VAC-528VAC, 44-66Hz		

Power Electric Tester

III. TH6600L Series Programmable Bidirectional DC Electronic Load

Specifications

Model		TH66750L-20-05	TH66750L-40-10	TH66750L-60-15
Rated Input (Load Mode)	Power	0-5kW	0-10kW	0-15kW
	Voltage	0-750V	0-750V	0-750V
	Current	0-20A	0-40A	0-60A
	Internal Resistance	1.2-2200Ω	0.6-1100Ω	0.4-740Ω
Minimum resolution of setpoint	Voltage	10mV	10mV	10mV
	Current	0.01A	0.01A	0.01A
	Power	1W	1W	1W
	Internal Resistance	0.01Ω	0.01Ω	0.01Ω
Minimum resolution of readback value	Voltage	10mV	10mV	10mV
	Current	0.01A	0.01A	0.01A
	Power	1W	1W	1W
	Internal Resistance	0.0001Ω	0.0001Ω	0.0001Ω
Setpoint accuracy 12Months (25°C±5°C)	Voltage	≤0.1% FS	≤0.1% FS	≤0.1% FS
	Current	≤0.2% FS	≤0.2% FS	≤0.2% FS
	Power	≤1% FS	≤1% FS	≤1% FS
	Internal Resistance	≤1% of maximum resistance ±1% of maximum current		
Readback accuracy 12Months (25°C±5°C)	Voltage	≤0.1% FS	≤0.1% FS	≤0.1% FS
	Current	≤0.2% FS	≤0.2% FS	≤0.2% FS
	Power	≤1% FS	≤1% FS	≤1% FS
	Internal Resistance	≤1% of maximum resistance ±1% of maximum current		
Ripple & Noise (20Hz-2MHz)	Differential Mode Voltage	≤800mVp-p and 200mVrms	≤800mVp-p and 200mVrms	≤800mVp-p and 200mVrms
	Differential Mode Current	≤16mArms	≤32mArms	≤48mArms
Remote Sensor Compensation		≤5%		
Energy Feedback Efficiency		≤93%		
Volume & Weight	Rack Mount(WxHxD)mm	430×133×703.5		
	Overall Dimension (WxHxD)mm	483×133×793.5		
	Weight (net weight)	18.5kg	25.5kg	32.5kg
Power Supply		342VAC-528VAC, 44-66Hz		

Power Electric Tester

III. TH6600L Series Programmable Bidirectional DC Electronic Load

Specifications

Model	TH661000L-40-15	
Rated Input (Load Mode)	Power	0-15kW
	Voltage	0-1000V
	Current	0-40A
	Internal Resistance	0.8-1300Ω
Minimum resolution of setpoint	Voltage	10mV
	Current	0.01A
	Power	1W
	Internal Resistance	0.01Ω
Minimum resolution of readback value	Voltage	10mV
	Current	0.01A
	Power	1W
	Internal Resistance	0.0001Ω
Setpoint accuracy 12Months (25°C±5°C)	Voltage	≤0.1% FS
	Current	≤0.2% FS
	Power	≤1% FS
	Internal Resistance	≤1% of maximum resistance ±1% of maximum current
Readback accuracy 12Months (25°C±5°C)	Voltage	≤0.1% FS
	Current	≤0.2% FS
	Power	≤1% FS
	Internal Resistance	≤1% of maximum resistance ±1% of maximum current
Ripple & Noise (20Hz-2MHz)	Differential Mode Voltage	≤1600mVp-p and 300mVrms
	Differential Mode Current	≤16mArms
Remote Sensor Compensation		≤5%
Energy Feedback Efficiency		≤93%
Volume & Weight	Rack Mount (WxHxD)mm	430×133×703.5
	Overall Dimension (WxHxD)mm	483×133×793.5
	Weight (net weight)	32.5kg
Power Supply		342VAC-528VAC, 44-66Hz